





Air Filter Regulator YT-200 / YT-205 / YT-220

Product Number: YT-200 / YT-205 / YT-220 (specify your requirement)

Model	Adjustable Range	Connection Type *	Gauge	Ambient Temp
YT-200	A 0~0.42Mpa	P PT	0 NONE	1 -20~70°C
YT-205	B 0~0.84Mpa	N NPT	1 0~0.4Mpa	2 -20~120°C
YT-220	C 0~0.21Mpa	* YT-205 is available for NPT1/4 connection type ONLY.		3 -40~70°C



Item · Type	YT-200	YT-220	YT-205	
	A	B	C	
Max. Supply Pressure	1.5MPa (15bar)			
Max. Output Pressure	0.42MPa (4.2bar)	0.84MPa (8.4bar)	0.21MPa (2.1bar)	
Air Connection	PT (NPT) 1/4	PT (NPT) 1/2	NPT 1/4	
Gauge Connection	PT (NPT) 1/4		NPT 1/4	
Ambient Temp.	-20~70°C (-4~158°F) (Standard type)			
Min. Filtering Size	5 micron			
Material	Aluminum Diecasting		Stainless Steel 316	
Weight	0.6kg (1.7lb)	0.86kg (1.89lb)	1.4kg (3.0lb)	



Air filter regulator YT-200, YT-205 suitably reduce plant's main air supply pressure and supplies to valve positioner(s) or control device(s).

- Maintain stable outlet pressure
- Light weight and compact size
- 5 micron filter
- Relief function - discharge pressure if outer pressure is higher than set pressure