





ES 65 Battery powered hydraulic cutting tool 65 mm dia.

Description

- > Cuts copper and aluminium cables with lightweight steel armouring (depending on cable type)
- > Also suitable for fine-stranded cables (depending on cable type)
- > Saves time with multiple cuts thanks to innovative opening mechanism
- > All tool data in view thanks to display and i-press® app

Characteristics

- > All data can be easily read via Bluetooth
- > Choose your battery system: Bosch or Makita
- > Open head, rotatable
- > Simple and safe: One-button operating concept for controlling all tool functions
- > Effortless working due to balanced centre of gravity
- > LED for work area illumination
- > 2-stage hydraulic system with fast feed and power stroke
- > Simple and safe: Automatic retraction when operation is complete
- > Manual retract stop (MRS) for efficient operations
- > Always ready-to-use thanks to battery charge and service display

Suitable for

> Cu and Al cable



Articles

| Battery powered hydraulic cutting tool 65 mm dia. with Bosch battery | | |
|---|---------|--|
| Part No. Bosch | ES65CFB | |
| Battery powered hydraulic cutting tool 65 mm dia. with Makita battery | | |
| Part No. Makita | ES65CFM | |

Technical Data

| | Bosch battery system | Makita battery system |
|----------------------|---------------------------------|---------------------------------|
| Head type | Cutter open | Cutter open |
| Cutting range | max. 65 mm dia. mm | max. 65 mm dia. mm |
| Cutting force | 40 kN | 40 kN |
| Cutting time | Depending on material thickness | Depending on material thickness |
| Number of cuts | Depending on material thickness | Depending on material thickness |
| Battery voltage (V) | 18 V | 18 V |
| Battery capacity | 5.0 Ah, Li-Ion | 4.0 Ah, Li-Ion |
| Charging time | 45 min. | 36 min. |
| Weight incl. battery | 6.3 kg | 6.3 kg |
| Ambient temperature | -10°C to +40 °C | -12°C up to +40 °C |